

- 1 1. A fan comprising:
  - 2 a rigid, rotatable drum-shaped housing having an interior and external circumference;
  - 3 rotatable propeller means disposed within said housing interior for forcing air
  - 4 therethrough;
  - 5 motor means within said housing interior for actuating said propeller means; and,
  - 6 rigid handle means coupled to said drum for rolling the fan.
- 7
- 8 2. The fan as defined in claim 1 further comprising bearing means for rotatably coupling
- 9 said handle means to said fan.
- 10
- 11 3. The fan as defined in claim 1 wherein the handle means can be rotated to an inverted
- 12 position whereby it functions as a support stand during fan operation.
- 13
- 14 4. The fan as defined in claim 1 wherein the handle means has a V-shaped configuration
- 15 with an apex to which the drum is mounted for rotation.
- 16
- 17 5. The fan as defined in claim 1 further comprising a recessed electrical plug to which
- 18 electricity may be selectively applied after the fan is set up to operate the motor means.
- 19
- 20 6. The fan as defined in claim 5 wherein the handle means has a V-shaped configuration
- 21 with an apex to which the drum is mounted for rotation that enables the handle to be inverted
- 22 to function as a support stand during fan operation.
- 23
- 24 7. The fan as defined in claim 1 wherein the motor means is located near the fan bottom to
- 25 stabilize and balance the fan.
- 26
- 27 8. The fan as defined in claim 1 wherein tires are formed about the external circumference of
- 28 said housing.
- 29
- 30